

## Semi Rotary Hand Fuel Transfer Pump

---

11-90ltr Per Min (approx.)



### About the product

The Semi Rotary [Hand Fuel Pump](#) is a popular choice for the manual transfer of diesel or water (depending upon the model) due to it being reliable, yet cost effective. This [diesel transfer pump](#) is available in a number of models with differing flow rates depending upon the user's requirements, whereas the water pump has a maximum of 24litres per minute.

- Manual Semi Rotary Diesel Hand Pump
- Max flow rate: 11-90ltr Per Min (depending on model)
- F BSP flanged inlet and outlet (size depends on model)
- Backplate Lugs

## Product models and features

Code	Model	Description	
CTS5010	K0 Semi Rotary Diesel Transfer Pump	Max Flow (lpm) – 11 Suction Inlet – ½" F BSP Flanged Dispensing Outlet – ½" F BSP Flanged Mounting – Backplate Lugs Suitable for diesel	
CTS5011	K1 Semi Rotary Diesel Transfer Pump	Max Flow (lpm) – 17 Suction Inlet – ¾" F BSP Flanged Dispensing Outlet – ¾" F BSP Flanged Mounting – Backplate Lugs Suitable for diesel	
CTS5000C	K2 Semi Rotary Diesel Transfer Pump	Max Flow (lpm) – 22 Suction Inlet – 1" F BSP Flanged Dispensing Outlet – 1" F BSP Flanged Mounting – Backplate Lugs Suitable for diesel	
CTS5012	K3 Semi Rotary Diesel Transfer Pump	Max Flow (lpm) – 29 Suction Inlet – 1 ¼" F BSP Flanged Dispensing Outlet – 1 ¼" F BSP Flanged Mounting – Backplate Lugs Suitable for diesel	
CTS5013	K4 Hi Flow Semi Rotary Diesel Transfer Pump	Max Flow (lpm) – 43 Suction Inlet – 1 ¼" F BSP Flanged Dispensing Outlet – 1 ¼" F BSP Flanged Mounting – Backplate Lugs Suitable for diesel	
CTS5014	K5 Semi Rotary Diesel Transfer Pump	Max Flow (lpm) – 53 Suction Inlet – 1 ½" F BSP Flanged Dispensing Outlet – 1 ½" F BSP Flanged Mounting – Backplate Lugs Suitable for diesel	
CTS5015	K7 Semi Rotary Diesel Transfer Pump	Max Flow (lpm) – 90 Suction Inlet – 2 F BSP Flanged Dispensing Outlet – 2 F BSP Flanged Mounting – Backplate Lugs Suitable for diesel	
CTS5020	Excelsior Bronze Semi Rotary Water Transfer Pump	Max Flow (lpm) – 24 Suction Inlet – 1" F BSP Flanged Dispensing Outlet – 1" F BSP Flanged Mounting – Backplate Lugs Suitable for water	