


# HYDRAULIC TRAILER BRAKE QUICK RELEASE COUPLINGS

Trailer Brake Quick Release Couplings are specialized hydraulic fittings designed for connecting and disconnecting the brake lines of trailers quickly and efficiently. These couplings ensure a secure and leak-free connection between the trailer's hydraulic brake system and the towing vehicle, providing both convenience and safety.

- Standard: ISO 5676
- Materials: Zinc Plated Carbon Steel Body
- Valve: Flat Poppet Type
- Seals: Standard in nitrile NBR. On request FKM & EDM Seals
- Back-up ring PTFE
- Working temperature with standard seals: -25°C + 125°C








#### FEMALE TRAILER BREAK QUICK RELEASE COUPLING


DN	ISO	L2	DI	S1	Π	PRODUCT REFERENCE
08	12.5	55.8	44	27	3/8" BSP	QRCTBF38
					1/2" BSP	QRCTBF12
					M18 X 1.5	QRCTBFM18



### MALE TRAILER BREAK QUICK RELEASE COUPLING WITH BULKHEAD CONNECTION

DN	ISO	u	L2	L3	L4	<b>S</b> 2	D2	Т2	PRODUCT REFERENCE
08	12.5	95.5	55.8	55	21	32	12	M18 X 1.5	QRCTBBMM18
		97.3		57	23		15	22 X 1.5	QRCTBBMM22

### **TECHNICAL DATA**



### MALE TRAILER BREAK QUICK RELEASE COUPLING WITH MALE THREAD


DN	ISO	u	L2	L3	L5	<b>S</b> 2	Т2	PRODUCT REFERENCE
08	12.5	91	55.8	48.0	15.0	32.0	1/2 " BSP	QRCTBM12

NOM	AINAL SIZE	МАХ	RATED FLOW	МІ	N BURST PRE	FLUID SPILLAGE	
		WORKING PRESSURE		MALE	FEMALE		COUPLED
DN	ISO	(BAR)	(L/M)	(BAR)	(BAR)	(BAR)	(cc)
04	6.3	400	12	1900	1900	1430	0.008
06	10	350	23	1560	1780	1610	0.01
08	12.5	350	45	1700	1590	1900	0.012
12	20	350	100	1660	1470	1840	0.02
16	25	350	189	1470	1400	1530	0.03
24	40	350	379	1000	1000	1000	0.25
32	50	250250	758	1000	1000	1000	0.35



## ACCESSORIES

Dust plugs for quick release couplings serve an important role in protecting the coupling from contaminants like dirt, moisture, and debris when not in use. By covering the exposed ends of the coupling, dust plugs help prevent damage to the internal components, ensure a proper seal, and maintain the overall functionality and longevity of the coupling. They also help maintain the cleanliness of the coupling, ensuring that it works efficiently when it is connected.



DN	ISO	FEMALE DUST PLUG	MALE DUST PLUG	COLOUR	MATERIAL
08	12.5		QRCTBMPVC	Grey	Plastic
08	12.5	QRCTBFS		Silver	Steel

